

CATEGORY	SHEAR CUT														SCORE CUT						RAZOR CUT		
	TOP THIN	TOP MANUAL			TOP EASY SETTING			ESSENTIAL			BASIC				EK1.25	EK1.25 CS	EK30	EKJ30	JCS3-TP48	J3H-TP48	HEAD	J3H-TL100	J3H-RB
MODEL	J1-19	J2-40C	J3L-48C	J3H-75C	J2B-40C	J3B-48C	J3B-75C	JS2-40C	JS3-48C	JS3-75C	J1.3PCS	JCS2-40C	JCS3-48C	JCS3-75C							TL 90	TL 105	TI 130
FEATURES																							
MIN SLIT (mm)	20	40	50	75	40	50	75	40	50	75	20	40	50	75	25	25	30	40	50	80	20/40/50	100	80
BLADE / RAZOR	ø90 ø105	ø90 ø105	ø130 ø150	ø130 ø150 ø180 ø200	ø90 ø105	ø130 ø150	ø130 ø180 ø200	ø90 ø105	ø130 ø150	ø130 ø150	ø90 ø105	ø90 ø105	ø130 ø150	ø130 ø150	ø100	ø100	ø100	ø100	ø130 ø150 ø180	ø130 ø150 ø180	razor b. 43x22x 0,3	razor b. 43x22x 0,3	razor b. stanley 60x19x 0,65
MAX SPEED (mpm)***	1000	1000	1500	2500	1000	1500	2500	600	1000	1200	1000	600	800	800	400	400	400	400	500	500	****	****	****
GUIDEBAR TIPE	3.15454.E	4.8579.E	4.8579.E	4.8579.E	4.318.E	4.318.E	4.318.E	4.7282.E	4.7283.E	4.7283.E	4.318.E	4.318.E	4.318.E	4.318.E	4.318.E	4.15454.E	4.318.E	4.8579.E	4.318.E	4.8579.E	**	4.8579.E	4.8579.E
VERTICAL FORCE	—	—	—	—	—	—	—	—	—	—	—	—	—	—	45kg	45kg	25kg	25kg	80kg	85kg	—	—	80kg
MATERIALS																							
PAPER (gsm)	≤ 250	≤ 300	≤ 600	≤ 1500	≤ 300	≤ 600	≤ 1500	≤ 350	≤ 600	≤ 800	≤ 250	≤ 350	≤ 600	≤ 800	✗	✗	✗	✗	✗	✗	✗	✗	✗
LAMINATE (gsm)	≤ 250	≤ 300	≤ 600	≤ 1500	≤ 300	≤ 600	≤ 1500	≤ 350	≤ 600	≤ 800	≤ 250	≤ 350	≤ 600	≤ 800	✗	✗	✗	✗	✗	✗	✗	✗	✗
PLASTIC FILM/ SHEET(mm)	≤ 0,6*	≤ 0,6	≤ 1	≤ 2*	≤ 0,6	≤ 1	≤ 2*	≤ 0,4	≤ 1	≤ 1,2	≤ 0,6	≤ 0,4	≤ 1	≤ 1,2	✗	✗	✗	✗	✗	✗	≤ 0,03	≤ 0,03	≤ 12
NONWOVEN (gsm)	≤ 300	≤ 400	≤ 600	≤ 1000	≤ 400	≤ 600	≤ 1000	≤ 400	≤ 600	≤ 800	≤ 300	≤ 400	≤ 600	≤ 800	▽	▽	▽	▽	▽	▽	✗	✗	✗
TEXTILE	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	✗	✗	✗
ALUMINIUM (mcr)	≤ 200	≤ 200	<500	<500	≤ 200	≤ 500	≤ 500	≤ 200	≤ 200	≤ 300	≤ 200	≤ 200	≤ 200	≤ 300	✗	✗	✗	✗	✗	✗	✗	✗	✗
RUBBER	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽	▽
FIBER GLASS. (gsm)	≤ 200	≤ 300	≤ 500	≤ 1000	≤ 300	≤ 500	≤ 1000	≤ 300	≤ 500	≤ 700	≤ 200	≤ 300	≤ 500	≤ 700	▽	▽	▽	▽	▽	▽	✗	✗	✗

▽ ASK FOR FEASIBILITY

✗ NON POSSIBLE